

Platform

0.91 m roll-out deck extension
 Fold-down handrails
 Self-closing gate
 Removable platform console box
 Lanyard attach points
 Full proportional drive joystick control with integral thumb steer switch
 Proportional lift/lower speed control
 Joystick enable for lift and drive
 Load sensing system
 Two speed drive selection

Power & Transmission

Two Wheel Direct Electric Drive
 8 x 6V 370 A/hr deep cycle batteries
 Automatic traction control
 Programmable "Personality" settings
 On-board self-diagnostic testing
 Detachable battery compartments
 23 amp automatic battery charger
 Automatic rear wheel brakes
 Sculptured ABS hoods

Functional Equipment & Accessories

3 degree tilt alarm and indicator light
 Steel scissor guards
 240/55 - 17.5 non marking foam filled tyres
 Oscillating rear axle
 Lifting/tie down lugs
 Lubrication free scissor arm bushings
 Scissor maintenance prop
 AC cable to platform
 Ground control selector switch with key lock
 Battery condition indicator
 Hour meter
 Horn
 Manual descent pull cable

Available Options

Hydraulic levelling jacks
 All motion alarm
 Descent alarm
 Alarm package ¹
 Platform work-lights
 Amber strobe light
 Plugs and Sockets

¹ Includes all-motion alarm and amber strobe light.

4069LE

A. Platform height – elevated	12.19 m
B. Platform height – lowered	1.73 m
C. Platform railing height ¹	1.10 m
D. Stowed height (rails folded)	2.04 m
E. Platform size	1.65 m x 2.92 m
F. Deck extension	0.91 m
G. Overall width ²	1.75 m
H. Overall length ²	3.07 m
I. Wheelbase	2.32 m
J. Ground clearance	0.20 m
Platform capacity	360 kg
Capacity on deck extension	120 kg
Lift/lower time	54/50 sec.
Maximum drive height	9.14 m
Machine weight ¹ ²	5,300 kg
Maximum ground bearing pressure	9.4 kg/cm ²
Drive speed – lowered	4.8 km/h
Drive speed – elevated	0.8 km/h
Gradeability	35%
Turning radius – inside	2.29 m
Turning radius – outside	4.88 m
Tyres (non-marking)	240/55-17.5
Brakes	Automatic Spring Applied
Drive motors	Dual Electric Traction
Hydraulic Pump Motor	Perm Magnet
Batteries	8 x 6V 370 A/hr
Charger (120/240V - 50/60HZ)	23 Amp SCR Automatic
Hydraulic pump	Gear Pump
Hydraulic system	32 L
Generator set	—
Generator fuel tank	—

¹ Certain weight and dimensions may vary due to options and to compliance with country standards.

² Dimensions with optional levelling jacks are; Length 3.73 m, Width 1.75 m, Weight +400kg.

Certain options or country standards may increase weight and/or dimensions.

